







©2018 Tactical UAS". Rapid Composites" is a Registered Trademark of Taylor & Lego Holdings, LLC. All rights reserved. Export of this product is regulated by the U.S. Department of State in accordance with guidelines of "International Traffic Arms Regulations (ITAR) per Title 22, Code of Federal Regulations, Parts 121-128



BULLRAY MINI



SPECIFICATIONS

Wingspan: 14.5" L x 10" W x 3.5" H
Installed Power: 2.4kW [X4 config.]

Max Takeoff Weight:4 poundsTypical Weight:24 ozEmpty Weight:16 ozPayload:32 ozBattery Weight:5.45 oz

Battery Capacity: 2.6 Ah [2 batteries X4 configuration]

Hover Time: 10-15 Minutes

Max Speed: Up to 70 mph

Typical Endurance: 3 Miles

Key Operational Capabilities: CQB, FLIR, mission planning, GPS denied space

Unique Features: Composite construction, grid fin lift surfaces

LUNGFISH - 3 ™



SPECIFICATIONS

Wingspan: 20" L x 19" W x 10.2" H
Installed Power: 5.1kW [X8 configuration]

Max Takeoff Weight: 7.5 pounds
Typical Weight: 72 oz
Empty Weight: 40 oz
Payload: 48 oz

Battery Weight: 32 oz

Battery Capacity: 10.6 Ah (2 batteries X8 config.)

Hover Time: 20-25 minutes **Max Speed:** Up to 100 MPH

Typical Endurance: 15 miles

Key Operational Capabilities: CQB, FLIR, mission planning, munitions, GPS denied space

Unique Features: Air foil lift surfaces and rotor-shroud, optionally amphibious

BULLRAY HEAVY ™

SPECIFICATIONS



Wingspan: 72" L x 72" W x 21-25" H

Installed Power: 16kW [X4 configuration] 32kW [X8 configuration]

Max Takeoff Weight: 100 pounds
Typical Weight: 35 pounds
Empty Weight: 23 pounds

Payload: 20 pounds [X4 configuration] 40 Pounds [X8 configuration]

Battery Weight: 12 Pounds [X4 configuration] 24 Pounds [X8 configuration]

Battery Capacity: 44Ah [2 batteries X4 configuration] 88Ah [2 batteries X8 configuration]

Hover Time: 20 minutes
Max Speed: Up to 70 mph
Typical Endurance: 10 Miles

Key Operational Capabilities: Amphibious, multi mission capable, multiple weapon/munitions

Unique Features: Re-configurable, massive payload, telescoping suspension skids